

LED HiPole X Tennis Court & Area Light SL-HB37



Overview

SL-HB37 Anole area/site family is available in two sizes as well as a variety of outputs allowing you to customize your lighting design to meet application requirements. Designed for sustained, long-term performance with advanced thermal management, an elegantly simple heat sink and industry leading surge protection, Anole brings the traditional shoebox practicality into the next generation of LED lighting.

- * Entry level 125lm/W & high configuration 140lm/W for option.
- * 100W / 150W / 200W / 300W, to replace 250W to 750W HID luminaires.
- * Delivers up to 42,000 lumens.
- * Full range of voltage 100-277V, 277-480VAC.
- * Type III and type V light distributions that covers the parking lots, and streets.
- * Photocell or Occupancy Sensor option dims product when space is not occupied.
- * External glare shield and bird spikes available.
- * Versatile mounting: Square or round pole mount, adjustable slip-fitter and wall mount.



Specifications

Series Code	SL-HB37
Power	100W, 150W, 200W, 300W
Efficacy	140lm/W, 160lm/W
Input Voltage	100-277VAC, 277-480VAC, 50 / 60 Hz
Power Factor	>0.92
Surge Protection	6kV line-line, 10kV line-earth
Control	Plug-and-play Microwave, PIR Sensor
IP Rating	IP66
IK Rating	IK08
CCT	5000K, 4000K
CRI	70, 80
Operating Temperature	-30°C to + 45°C
Beam Angle	R21601, R21602
Mounting Option	integral slipfitter, Yoke, Square pole, Round pole