Light **FEEL**

Multi-pin power cable

















Order Code	AL-2PIN-22	AL-2PIN-20	AL-2PIN-18	AL-3PIN-22	AL-3PIN-20	AL-3PIN-18	AL-4PIN- 22	AL-4PIN- 20	AL-4PIN- 18	AL-5PIN- 22	AL-5P I N- 20	AL-5P I N- 18	AL-6P I N- 22	AL-6PIN- 20	AL-6PIN- 18
Style/Type:	1007 AWM	1007 AWM	1007 AWM	1007 AWM	1007 AWM	1007 AWM	1007 AWM	1007 AWM	1007 AWM	1007 AWM	1007 AWM	1007 AWM	1007 AWM	1007 AWM	1007 AWM
Rated Voltage:	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V
Wire Gauge:	22AWG	20AWG	18AWG	22AWG	20AWG	18AWG	22AWG	20AWG	18AWG	22AWG	20AWG	18AWG	22AWG	20AWG	18AWG
Conductor Material:	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper
Cross Sectional Area:	0.3mm²	0.5mm ²	0.75mm²	0.3mm²	0.5mm ²	0.75mm ²	0.3mm ²	0.5mm ²	0.75mm ²	0.3mm ²	0.5mm ²	0.75mm ²	0.3mm ²	0.5mm ²	0.75mm²
Outer Diameter:	1.6mm	1.8mm	2.1mm	1.6mm	1.8mm	2.1mm	1.6mm	1.8mm	2.1mm	1.6mm	1.8mm	2.1mm	1.6mm	1.8mm	2.1mm
Number of Cores:	2	2	2	3	3	3	4	4	4	5	5	5	6	6	6
Core strands:	17/0.12TS	21/0.14TS	34/0.14TS	17/0.12TS	21/0.14TS	34/0.14TS	17/0.12TS	21/0.14TS	34/0.14TS	17/0.12TS	21/0.14TS	34/0.14TS	17/0.12TS	21/0.14TS	34/0.14TS
Insulation Material:	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC
Rated Temperature:	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }
Color:	Red+Black/Blu e+Brown / Other customized colors	Red+Black/Bl ue+Brown / Other customized colors	Red+Black/Blu e+Brown / Other customized colors	Brown+Whit e+Yellow / Other customized colors	Brown+Whit e+Yellow / Other customized colors	e+Ye ll ow / Other	+Blue+Blac k / Other	+Blue+Blac k / Other		Red+Green +Blue+Whi te+Black / Other customized colors	Red+Green +Blue+Whi te+Black / Other customized colors		Red+Green +Blue+Whi te+Yellow+ Black / Other customized colors	Red+Green +Blue+Whi te+Yellow+ Black / Other customized colors	+Blue+Whi te+Yellow+ Black / Other
Standard Package:	500m/roll	500m/ro ll	500m/ro ll	250m/ro ll	250m/ro ll	250m/ro ll	250m/ro ll	250m/ro ll	250m/ro ll	250m/ro ll	250m/ro ll	250m/ro ll	250m/ro ll	250m/ro ll	250m/ro ll
Compliance/Certi fications:	UL/VDE	UL/VDE	UL/VDE	UL/VDE	UL/VDE	UL/VDE	UL/VDE	UL/VDE	UL/VDE	UL/VDE	UL/VDE	UL/VDE	UL/VDE	UL/VDE	UL/VDE
Appilications:	LED lightings,Comp uter and office equipment, Household appliances, etc	LED lightings,Com puter and office equipment, Household appliances, etc	LED lightings,Comp uter and office equipment, Household appliances, etc			LED lightings,Co mputer and office equipment, Household appliances, etc	LED lightings,Co mputer and office equipment, Household appliances, etc	omputer and office equipment,	mputer and office equipment,	mputer and office equipment, Household	mputer and office equipment,	mputer and office equipment, Household	mputer and office equipment,		mputer and office equipment, Household



Multi-core Insulated PVC power cable







Order Code	AL-PVC-2PIN- 22	AL-PVC-2PIN- 20	AL-PVC-2PIN- 18	AL-PVC- 3PIN-22	AL-PVC- 3PIN-20	AL-PVC- 3PIN-18	AL-PVC- 4PIN-22	AL-PVC- 4PIN-20	AL-PVC- 4PIN-18	AL-PVC- 5PIN-22	AL-PVC- 5PIN-20	AL-PVC- 5PIN-18	AL-PVC- 6PIN-22	AL-PVC- 6PIN-20	AL-PVC- 6PIN-18
Style/Type:	2464 AWM	2464 AWM	2464 AWM	2464 AWM	2464 AWM	2464 AWM	2464 AWM	2464 AWM	2464 AWM	2464 AWM	2464 AWM	2464 AWM	2464 AWM	2464 AWM	2464 AWM
Rated Voltage:	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V	300V
Wire Gauge:	22AWG	20AWG	18AWG	22AWG	20AWG	18AWG	22AWG	20AWG	18AWG	22AWG	20AWG	18AWG	22AWG	20AWG	18AWG
Conductor Material:	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper	bare copper
Cross Sectional Area:	0.3mm²	0.5mm²	0.75mm²	0.3mm²	0.5mm²	0.75mm²	0.3mm²	0.5mm²	0.75mm²	0.3mm²	0.5mm²	0.75mm²	0.3mm²	0.5mm²	0.75mm²
Outer Diameter:	4.2mm	4.6mm	5.2mm	4.4mm	4.8mm	5.5mm	4.7mm	5.2mm	6.0mm	5.5mm	6.5mm	7.3mm	5.8mm	6.9mm	7.8mm
Number of Cores:	2	2	2	3	3	3	4	4	4	5	5	5	6	6	6
Core strands:	17/0.16TS	21/0.178TS	34/0.178TS	17/0.16TS	21/0.178TS	34/0.178TS	17/0.16TS	21/0.178TS	34/0.178TS	17/0.16TS	21/0.178T S	34/0.178TS	17/0.16TS	21/0.178TS	34/0.178TS
Insulation Material:	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC	PVC
Rated Temperature:	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }	{ -20°C - 80°C }
Core Color:	Red+Black/Blue +Brown / Other customized colors	Red+Black/Blu e+Brown / Other customized colors	Red+Black/Blue +Brown / Other customized colors	Brown+Whit e+Yellow / Other customized colors	Brown+Whit e+Yellow / Other customized colors	Brown+Whit e+Yellow / Other customized colors	Red+Green+ Blue+Black / Other customized colors	Red+Green+ Blue+Black / Other customized colors	Red+Green +Blue+Blac k / Other customized colors	Red+Green +Blue+Whit e+Black / Other customized colors	Red+Gree n+Blue+W hite+Black / Other customize d colors		Red+Green+ Blue+White+ Yellow+Black / Other customized colors	Red+Green +Blue+Whit e+Yellow+Bl ack / Other customized colors	Red+Green+E lue+White+Ye llow+Black / Other customized colors
Outside PVC Color	Black/White/Oth er customized colors	Black/White/Ot her customized colors	Black/White/Ot her customized colors	Black/White/ Other customized colors	Black/White/ Other customized colors	Black/White/ Other customized colors	Black/White/ Other customized colors	Black/White/ Other customized colors	Black/White /Other customized colors	Black/White /Other customized colors	Black/Whit e/Other customize d colors	Black/White /Other customized colors	Black/White/ Other customized colors	Black/White /Other customized colors	Black/White/C ther customized colors
Standard Package:	300m/roll	300m/roll	100m/ro ll	200m/ro ll	200m/roll	100m/roll	200m/ro ll	200m/roll	100m/roll	200m/roll	100m/ro ll	100m/ro ll	200m/ro ll	100m/ro ll	100m/roll
Compliance/Certific ations:	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL
Appilications:	LED lightings,Compu ter and office equipment, Household appliances, etc	LED lightings,Comp uter and office equipment, Household appliances, etc	LED lightings,Comp uter and office equipment, Household appliances, etc	LED lightings,Co mputer and office equipment, Household appliances, etc	LED lightings,Co mputer and office equipment, Household appliances, etc	LED lightings,Co mputer and office equipment, Household appliances, etc	LED lightings,Com puter and office equipment, Household appliances, etc	LED lightings,Co mputer and office equipment, Household appliances, etc		LED lightings,Co mputer and office equipment, Household appliances, etc	LED lightings,C omputer and office equipment, Household appliances, etc	mputer and office , equipment, Household	LED lightings,Co mputer and office equipment, Household appliances, etc	LED lightings,Co mputer and office equipment, Household appliances, etc	LED lightings,Com puter and office equipment, Household appliances, etc